

## Amendments to the Claims

**Please amend the claims as follows:**

1. (Currently Amended) A VSB reception system comprising:
  - a demodulating part for receiving, converting, and demodulating a signal;
  - a frequency domain equalizing part for equalizing the demodulated signal for removing a distorted component from the demodulated signal; and
  - a noise removing part for (a) receiving the equalized signal, (b) calculating a reference error signal that is a difference between the equalized signal and a signal having noise extracted therefrom ~~the signal having the noise removed therefrom~~, (c) receiving the reference error signal and a noise signal extracted from the equalized signal at a first operator which calculates ~~calculating~~ an error signal that is a difference between the reference error signal and the noise signal extracted from the equalized signal, ~~the extracted noise signal~~, (d) renewing parameters with reference to the reference error signal and the error signal, and (e) calculating a difference between the equalized signal and the extracted noise signal, to provide the signal ~~a signal~~ having the noise extracted ~~removed~~ therefrom.
2. (Original) The VSB reception system as claimed in claim 1, wherein the demodulating part carries out tuning to a desired channel from received RF (Radio Frequency) signals, converting a RF signal on the tuned channel into an IF (Intermediate Frequency) signal, and demodulating the IF signal in reverse of a VSB modulating method.

3. (Original) The VSB reception system as claimed in claim 1, wherein the frequency domain equalizing part carries out converting a received time domain signal into the frequency domain signal, equalizing the frequency domain signal, and converting the equalized frequency domain signal into a time domain signal.

4. (Original) The VSB reception system as claimed in claim 1, wherein the frequency domain equalizing part carries out assuming a channel impulse response from a received time domain signal, converting the assumed channel impulse response and the time domain signal into frequency domain signals respectively, renewing parameters with reference to the converted frequency domain signal, to correct a distortion of the frequency domain signal, and converting the frequency domain signal having the distortion therein corrected into a time domain signal.

5. (Currently Amended) The VSB reception system as claimed in claim 1, wherein the noise removing part includes;

a first ~~second~~ operator for calculating a difference between signals from/to the noise removing part, to provide ~~a reference~~ the reference error signal,

~~a second operator for calculating a difference between the reference error signal and the extracted noise signal, to provide an error signal,~~

a filtering part for renewing parameters with reference to the reference error signal from the ~~first~~ second operator and the error signal from the ~~second~~ first operator, to extract the noise ~~a noise~~ signal, and

a third operator for calculating a difference between a signal from the noise removing part and the noise signal extracted at the filtering part to provide the signal ~~a signal~~ having the noise extracted ~~removed~~ therefrom.

6. (Currently Amended) The VSB reception system as claimed in claim 5, further comprising a deciding part between the ~~first~~ second operator and the third operator for making decision with reference to a signal from the third operator.

7. (Original) The VSB reception system as claimed in claim 6, wherein the deciding part is a VSB slicer.

8. (Currently Amended) The VSB reception system as claimed in claim 5, wherein the noise removing part further includes;

a first delay for delaying, and forwarding a signal received at the noise removing part to the ~~first~~ second operator,

a second delay for delaying, and forwarding a signal from the third operator to the second operator ~~first delay~~, and

a third delay for delaying, and forwarding the noise signal extracted at the filtering part to the first operator.

9. (Original) The VSB reception system as claimed in claim 5, wherein the filtering part is an LMS (Least Mean Square) filter for renewing the parameters by LMS method.

10. (Original) The VSB reception system as claimed in claim 9, wherein the renewal of the parameters by LMS method uses the following equation.

$$c(k, n+1) = c(k, n) + u * e(n) * x(k, n)$$

where, 'n' denotes 0, 1, 2, ----, and 'k' denotes a (k)th tap parameter. 'u' denotes a constant for fixing a magnitude of a renewed value, 'e(n)' denotes a received error value, 'x(k, n)' denotes an input value of a (k)th tap at a time 'n'.

11. (Original) The VSB reception system as claimed in claim 5, wherein the first, second, and third operators are subtractors or adders.

### **Amendments to the Drawings**

The Office Action suggests changing the term “Related Art” to “Prior Art” in Figs. 1, 2A, 2B, 3A, and 3B. The substitute drawing figures enclosed herein include the suggested changes.